




## CREATE A STRIKING CUSTOM SHOWPIECE FROM THE FLOOR UP USING GENUINE OAK PARQUETRY ENGINEERED FLOORING.

Each block of Genuine Oak Parquetry is carefully constructed using Genuine French Oak lamella for the wear layer, which is bonded to a strong Eucalyptus plywood core and reinforced with a veneer backing. This type of construction ensures product stability and quality assurance.









## GENUINE OAK PARQUETRY PROVIDES A CONTEMPORARY HERRINGBONE PATTERN WITH COLOUR OPTIONS TO REFLECT ONE'S PERSONAL TASTE OR STYLE.

Such a grand floor selection is made easy in the modern day with six traditional and timeless prefinished stain colours available. 7 coats of UV cured Treffert Lacquer system are applied to complete this exquisite flooring.





Core Material:  Plantation Eucalypt Plywood  Profile / Lock:  Tongue & Groove (Ends & Sides)  Width:  150mm  Thickness:  15mm  Wear Layer:  4mm  Length:  600mm	
Width: 150mm  Thickness: 15mm  Wear Layer: 4mm	
Thickness: 15mm  Wear Layer: 4mm	
Wear Layer: 4mm	
,	
Length: 600mm	
Coating / Finish: UV Cured 7 Coat Treffert Lacquer System	
Coverage per Box: 1.08m² per Box	
Packaging: 12 Pieces per Box, 60 Boxes per Pallet	













## Auckland

Unit 11 / 18 Corinthian Drive, Albany, Auckland 0632 - BY APPOINTMENT ONLY Phone: 0800 HURFORD (0800 4873673) Email: info@hurfordflooring.co.nz Tauranga 50 Hull Road, Mt Maunganui, New Zealand, 3150

